

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	ThinkCentre Logo			
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs			
	Alvin L Carter	, -		
	1009 Think Place Pullilian 9 (554)			
	Building 2 / 5F1			
	Morrisville, North Carolina 27560			
	carter@lenovo.com			
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html			
Additional information	The latest version of this document can be found at			
	http://www.lenovo.com/social_responsibility/us/en/datasheets_ne	otebooks.html		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Personal Computer						
Commercial name *	ThinkCentre M73 Tower						
Model number *	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK						
Issue date *	2015-05-05						
Intended market *	Global Europe Asia, Pacific & Japan Americas Other						
Additional information	ENERGY STAR® 6.1 Qualified (10B1, 10B2, 10HJ, 10HK); EPEAT Gold Rating (10B1, 10B2, 10HJ, 10HK); GreenGuard						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	ent met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control suc as organized by IT-Företagen (see www.itecodeclaration.org).	h 🔀	

Model number *	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK		
Issue date *	2015-05-05	Logo	lenovo.

Product	Product environmental attributes - Legal requirements				
Item		Yes	No	n.a.	
P1	Hazardous substances and preparations				
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)				
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide				
	(see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).				
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)				
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).				
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998. REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/materials.html				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more				
. 2.1	than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)				
P3	Safety, EMC connection to the telephone network and labeling				
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\boxtimes			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).				
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes			
P4	Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).				
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes	
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).				
P5	Product packaging				
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.				
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).				
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protoco (see legal reference). Comment: Legal reference has no maximum concentration values.				

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK		
Issue date *	2015-05-05	Logo	lenovo.

Product	environmental attributes - Market requirements - Environmental conscious design Re	quire	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.			
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.			
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: ABS Material type: PC/ABS Material type: Steel			
P7.12	Electrical cable insulation materials of power cables are PVC free.	<u>Ц</u>	\boxtimes	
P7.13	Electrical cable insulation materials of signal cables are PVC free		\boxtimes	
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.	\boxtimes		
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14			
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in	П	П	\boxtimes
	concentrations above 0.1%:	_		
	Comment: No legal limits exist, this is a market requirement.			
	1. Chemical name: , CAS #: 2. Chemical name: , CAS #:			
	3. Chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
D7.40	Distinct Of the feet for the state of the between the state of the sta		<u> </u>	
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	<u> </u>	Ш	
P7.20	Of total plastic parts' weight >25g, recycled material content is 43.15% . (contains keyboard, mouse and power code)			
P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.			
P7.22	Light sources are free from mercury			
P8	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg Batteries mg			
P8.1*	Battery chemical composition:			
P8.2	Batteries meet the requirements of the following voluntary program/s:			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK		
Issue date *	2015-05-05	Logo	lenovo

roduct environmental attributes - Market requirements (continued)			Requirement	t	
Item				Yes No	n.a.
P9 Energy consumption	on			Tes No	II.a.
	ollowing power levels	or energy consur	nptions are repor	ted: See P14	
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Category 0	l l		ı		1
Short Idle State - WOL Enabled	y W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Long Idle State - WOL Enabled	, W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Sleep (S3) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(P _{Sleep})	
Sleep (S3) - WOL Disabled	W	W	W	Reference	
Off (S5) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(Poff)	
Off (S5) - WOL Disabled	W	W	W	Use for EuP	
Category I1		·	<u>I</u>		1
Short Idle State - WOL Enabled	25.57 W	25.54 W	24.96 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	1 24.33 W	24.06 W	24.65 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	<i>0.68</i> W	0.71 W	0.87 W	Use for Energy Star V6.0 registration (Psleep)	
Sleep (S3) - WOL Disabled	0.68 W	0.71 W	0.87 W	Reference	
Off (S5) - WOL Enabled	0.43 W	0.45 W	0.62 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.31 W	0.31 W	0.31 W	Use for EuP	
Category I2	1	•	•		
Short Idle State - WOL Enabled	d 25.09 W	25.05 W	24.91 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	23.77 W	23.83 W	23.60 W	Use for Energy Star V6.0 registration(P _{Longidie})	
Sleep (S3) - WOL Enabled	0.69 W	0.70 W	0.87 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.68 W	0.70 W	0.87 W	Reference	
Off (S5) - WOL Enabled	0.44 W	0.46 W	0.62 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.31 W	0.31 W	0.31 W	Use for EuP	
Category I3		1	I		
Short Idle State - WOL Enabled	d 25.59 W	25.52 W	25.05 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	24.20 W	24.08 W	24.54 W	Use for Energy Star V6.0 registration(P _{Longidie})	
Sleep (S3) - WOL Enabled	0.69 W	0.71 W	<i>0.88</i> W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.68 W	0.70 W	<i>0.87</i> W	Reference	
Off (S5) - WOL Enabled	0.44 W	0.46 W	0.62 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.31 W	0.31 W	0.31 W	Use for EuP	
Category D1			I	1	
Short Idle State - WOL Enabled	d 33.74 W	33.55 W	33.31 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	32.70 W	32.53 W	32.45 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.69 W	0.70 W	<i>0.87</i> W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.68 W	0.70 W	0.87 W	Reference	
Off (S5) - WOL Enabled	0.44 W	0.46 W	0.62 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.31 W	0.31 W	0.31 W	Use for EuP	
Category D2	L	1	ı	•	
Short Idle State - WOL Enabled	d 34.14 W	33.89 W	33.84 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	33.08 W	32.84 W	32.82 W	Use for Energy Star V6.0 registration(PLongidie)	
Sleep (S3) - WOL Enabled	0.67 W	0.71 W	0.88 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.68 W	0.70 W	0.87 W	Reference	
Off (S5) - WOL Enabled	0.44 W	0.46 W	0.62 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.31 W	0.31 W	0.31 W	Use for EuP	

plugged in	oad bower supply / charger the wall outlet but ted from the product.)	W	W	W		
TEC Typical En	nergy Consumption	kWh/week	kWh/week	kWh/week		
ETEC * Annual En	ergy Consumption	Cat I1: 112.40; Cat I2: 110.19; Cat I3: 112.28; CatD1:148.45; CatD2:150.16 kWh/year	Cat I1: 112.04; Cat I2: 110.23; Cat I3: 112.00; CatD1:147.72; CatD2:149.17 kWh/year	Cat I1:111.75; Cat I2:110.22; Cat I3:111.89; CatD1:147.59; CatD2:149.71 kWh/year P _{sleep} : Sleep Mode(\$	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45 + P_{sleep} \times 0.05 + P_{ShortIdle} \times 0.35 + P_{LongIdle} \times 0.15)$ 63) - WOL Enabled; P_{idle} : Idle State - WOL Enabled	
Display ro	solution* : Me	gapixels				
. ,						
Print Spee	ed * : Ima	iges per minute				\boxtimes
Default tim	ne to enter energy save	mode: 30 minutes				
P9.2*	Information about the	e energy save function	n is provided with	the product.		
P9.3*		he energy requirement ersion: Version 6.0 a			/s: category: <i>I1,I2,I3,D1,D2</i>	
P10	Emissions					
	Noise emission – D	Declared according to	ISO 9296			
P10.1	Mode M	lode description		Declared A-weighted sound power		
				level $L_{W extsf{Ad}}$ (E	Bystander positions Desktop (only if product is not operator attended)	
	Idle *	HDD:Idle	DD:Idle * 3.3		25	
	Operation *	HDD: Operating	DD: Operating * 3.4		26	
	Other mode					
	Measured according	to: ISO7779 Other	ECMA-74 (only if not cove	red by ECMA-74 wi	th L _{pAm} measurement distance m)	
P10.2	The product meets t	he acoustic noise req				\boxtimes

Model nur	nber *	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK				
Issue date	*	2015-05-05	Logo	leno	VO.	
Product of met	environr	mental attributes - Market requirements (continued)		Require	ment	
Item				Yes	No	n.a.
	Chemica	al emissions from printing products				
P10.3*	Test perf	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify:				\boxtimes
P10.4		mission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC				
P10.5	Chemica [ll emission requirements of the following voluntary program/s are met for : Oust Ozone Styrene Benzene	TVOC 🗌			
D40.0		nagnetic emissions				
P10.6	program/		ig voluntary			
P11		able materials for printing products				
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required	, ,			\boxtimes
P11.2*	Paper control EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets that.	ne requirements o	f		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.				\boxtimes
P12	Ergonor	nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technologies				\boxtimes
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				\boxtimes
P13		ng and documentation				
P13.1*	Product	packaging material type(s): Corrugated paper weight (kg): 1.42 packaging material type(s): Fabricated PE weight (kg): 0.3 packaging material type(s): HDPE weight (kg): 0.016				
P13.2*	Product	plastic packaging is free from PVC.		\boxtimes		
P13.3*		nedia for user and product documentation (tick box): c 🔲, Paper 📐, Other 🗌				
P13.4*		r user and product documentation, please specify contained percentage of post-consu	mer recycled fiber:			
P14		nal information (See Note B4)				
	informati available approxim	Supplier makes no representations, guarantees, assurances or warranties whether expron contained in this document. All information provided by supplier in this document is at the time of completion, and supplier shall have no obligation to update such informational purposes only. See a Lenovo Account Representative.	provided based on tion. The information	supplier's on provide	know	
P9		rgy Star Qualified Notebooks & Tablet Computers for the latest information: ww.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&	pgw_code=CO			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkCentre M73	Logo
Model Number	10B0, 10B1, 10B2, 10B3, 10HJ, 10HK	lenovo
Issue Date	2015-05-05	
Additional information	Only 10B1, 10B2, 10HJ, 10HK is Erp Lot3 Qualified, which is equipped with ES PSU.	

(d)	Year of manufacture:		Δv	ailible on product labe			
(e)	E TEC value (kWh) and capabili	tv adjustments applied when all d	iscrete graphics cards (dGfx) are	amble on product labe			
-,	disabled and if the system is tested with switchable graphics mode with UMA driving the display:						
	Cat. B 91.91						
	Cat. C 91.52						
f)	Cat. D 94.92 E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (dGfx) are						
(1)	enabled:						
	Cat. B 121.89						
	Cat. C 121.87						
	Cat. D 123.15						
(g)	idle state power demand (Watts);						
				34.15			
(h)	sleep mode power demand (Watts);						
				1.25			
(i)	sleep mode with WOL enabled p	ower demand (Watts) (where enal	oled);	1.25			
··\							
(j)	off mode power demand (Watts);			0.57			
(k)	off mode with WOL enabled now	er demand (Watts) (where enable	4).				
` '							
(I)	Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):						
	10% 78.61% 20% 84.02% 50% 86.51% 100% 83.02%						
(m)							
	External power supply efficiency (if applicable):						
	10% 20% 50% 100% Average ;						
	or Level:						
(o)	The minimum number of loading	A1/A					
				N/A			
(f)	Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for						
	, ,, ,	or					
	electrical testing: Test voltage in V and frequency i						
	Total harmonic distortion of the electricity supply system <2%						
	Information and documentation on the instrumentation, set-up and circuits used for electrical testing						
	Instrument	Range Used	Make and Model **				
	Туре	Or ***	Make allu Model				
	AC Power Source	1~280VAC;1~550HZ;1000VA	NF;EC1000S; SN:9152124				
	Digital Watch	Full range	CASIO; HS-70W; SN:208Q08R				

(p-1) The mean (p-2) The mean (p-3) The mean (p-4) The mean as defined (q) Sequence (r) Descript (s) Sequence (t) The durn condition	asurement methodology uses as a surement methodology uses as a surement methodology used in Point P9.1 in the Professional P9.1 in the P9.1 in the Professional P9.1 in the P9.1 in the Professional P9.1 in the P9.1	used to determine information in N/A used to determine information in N/A used to determine information in N/A used to determine information in roduct IT Eco Declaration: 623 / IEC EN50564:2011 mea a stable condition with respect Power on -> Wait 5 minutes of mode was selected or progregin menu -> Power -> Selected	mentioned in points (m) – external PSU efficiency: mentioned in points (o) – loadingcycles batteries: mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: ->Stable condition fammed: et sleep or off mode pment automatically changes to sleep and/or off	
(p-1) The mean (p-2) The mean (p-3) The mean (p-4) The mean as defined (q) Sequence (r) Descript (s) Sequence (t) The durn condition	ermal anemometer Light Measuring assurement methodology casurement m	0~20m/s,-20~70°C 1°;1-300cd/m² Jused to determine information in 80 PLUS® Programmed to determine information in N/A Jused to determ	Testo;425;SN:02591883 Konica Minolta;LS-110; mentioned in points (I) – internal PSU efficiency: gram mentioned in points (m) – external PSU efficiency: mentioned in points (o) – loadingcycles batteries: mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: >>Stable condition rammed: cit sleep or off mode prement automatically changes to sleep and/or off	
(p-1) The mean of	Light Measuring assurement methodology to ed in Point P9.1 in the Proceed of Steps for achieving assurement methodology to ed in Point P9.1 in the Proceed of Steps for achieving assurement methodology to ed in Point P9.1 in the Proceed of Steps for achieving assurement methodology to ed in Point P9.1 in the Proceed of Steps for achieving assurement methodology to edition of how sleep and/or control of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for achieving assurement methodology to edition of the Proceed of Steps for	used to determine information in 80 PLUS® Programment N/A used to determine information in N/A used to det	Monica Minolta;LS-110; mentioned in points (I) – internal PSU efficiency: gram mentioned in points (m) – external PSU efficiency: mentioned in points (o) – loadingcycles batteries: mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: >>Stable condition rammed: et sleep or off mode prement automatically changes to sleep and/or off	
(p-1) The mean (p-2) The mean (p-3) The mean (p-4) The mean as defined (q) Sequence (s) Sequence (t) The durn condition	asurement methodology uses as a surement methodology uses as a surement methodology uses as a surement methodology used in Point P9.1 in the Properties of Steps for achieving as a surement methodology used in Point P9.1 in the Properties of Steps for achieving as a surement methodology uses a surement methodology uses a surement methodology uses as a surement methodology uses as a surement methodology uses a surement m	used to determine information in 80 PLUS® Programmenu -> Power -> Selections and PLUS® Programmenu information in N/A used to determine information in N/A used to determine information in roduct IT Eco Declaration: 623 / IEC EN50564:2011 means a stable condition with respect Power on -> Wait 5 minutes -> Power on -> Selection in the second in the	mentioned in points (I) – internal PSU efficiency: mentioned in points (m) – external PSU efficiency: mentioned in points (o) – loadingcycles batteries: mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: >>Stable condition rammed: et sleep or off mode prenent automatically changes to sleep and/or off	
(p-3) The means as defined (p-4) The means as defined (q) Sequence (r) Descript (s) Sequence (t) The dure condition	asurement methodology used in Point P9.1 in the Price of steps for achieving action of how sleep and/or of the price of events required to receive as a surement methodology uses a surement methodology	used to determine information in N/A used to determine information in roduct IT Eco Declaration: 623 / IEC EN50564:2011 mea a stable condition with respect Power on -> Wait 5 minutes -> off mode was selected or progregin menu -> Power -> Selected each the mode where the equi	mentioned in points (o) – loadingcycles batteries: mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: ->Stable condition rammed: et sleep or off mode pment automatically changes to sleep and/or off	
(p-4) The means defined as define	asurement methodology used in Point P9.1 in the Prince of Steps for achieving action of how sleep and/or of the Beautier of Events required to receive the sure of Events required to the sure of Event	wised to determine information in roduct IT Eco Declaration: 623 / IEC EN50564:2011 means a stable condition with respect a stable condition with respect off mode was selected or programmenu -> Power -> Selected on the mode where the equipment in the roduct of the ro	mentioned in maximum, idle, sleep, off mode power asurement methodology to power demand:: >Stable condition rammed: et sleep or off mode prenent automatically changes to sleep and/or off	
as define (q) Sequence (r) Descript (s) Sequence mode: (t) The dur condition	ce of steps for achieving a step and/or of the step	roduct IT Eco Declaration: 623 / IEC EN50564:2011 mea a stable condition with respect Power on -> Wait 5 minutes off mode was selected or progregin menu -> Power -> Selected each the mode where the equip	to power demand:: ->Stable condition	
(r) Descript (s) Sequence mode: (t) The dure condition	ce of steps for achieving a feation of how sleep and/or or Becce of events required to re	a stable condition with respect Power on -> Wait 5 minutes off mode was selected or progregin menu -> Power -> Selected each the mode where the equip	to power demand:: ->Stable condition rammed: et sleep or off mode pment automatically changes to sleep and/or off	
(r) Descript (s) Sequence mode: (t) The dure condition	tion of how sleep and/or or Becce of events required to re	Power on -> Wait 5 minutes of mode was selected or progregin menu -> Power -> Selected or progreach the mode where the equip	rammed: ct sleep or off mode pment automatically changes to sleep and/or off	
(s) Sequence mode: (t) The dure condition	tion of how sleep and/or or Becce of events required to re	off mode was selected or progregin menu -> Power -> Selected or progregin menu -> Selected or	rammed: ct sleep or off mode pment automatically changes to sleep and/or off	
(s) Sequence mode: (t) The dure condition	Becce of events required to re	egin menu -> Power -> Select each the mode where the equi	pment automatically changes to sleep and/or off	
(t) The dur condition	ce of events required to re	each the mode where the equi	pment automatically changes to sleep and/or off	
(t) The dur condition				
(t) The dur condition	Control Panel->Power	Options-> Change Settings	Bootons defects estimated and in other	
condition			-> Restore default settings for this plan	
(u) The len			utomatically reaches sleep mode, or another requirements for sleep mode (in minutes):	30 minutes
		od of user inactivity in which demand requirement than sleep	n the computer automatically reaches a power of mode (in minutes):	45 minutes
(v) The len	gth of time before the c	display sleep mode is set to	activate after user inactivity (in minutes):	15 minutes
(w) Informat	ion on the energy-saving	potential of power management	nt functionality:	
		N/A		
(x) User info	ormation on how to enabl	le the power management fund	ctionality:	
		Refer to User G	Guide	
	Battery Information:			
			/ies that cannot be accessed and replaced by a nor	
Additional informat	tion			