



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Computer Monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo				
Company name *	Lenovo					
Contact information *	Lenovo Global Environmental Affairs		Lenovo			
e-mail address	Alvin L Carter		LCIIOVO			
	alcarter@lenovo.com					
Internet site *	ttp://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information						

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Monitor				
Commercial name *	ThinkVision L24i-10				
Model number *	65D6				
Issue date *	2017/4/5				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model number * 65D6		65D6 L	.ogo	000			
Issue dat	e *	2017/4/5		Lenc)VC) _{TM}	
Product	environ	mental attributes - Legal requirements	F	Require	ment	met	
Item		• ,		Yes	No	n.a.	
P1	Hazardo	ous substances and preparations					
P1.1*	Products	s do comply with current European RoHS Directive. (See legal reference and NOTE E	31)	\boxtimes			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.						
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		\boxtimes			
	hydrobro	omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachlo	ride, 1,1,1-				
	concentr	ethane, methyl bromide (see legal reference). Comment: Legal reference has no ma: ration values.					
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlovl (PCT) in preparations (see legal reference).					
P1.5*		s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbo ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	n atoms in the				
P1.6*		th direct and prolonged skin contact do not release nickel in concentrations above 0,5	μg/cm²/week			\boxtimes	
		al reference).					
P1.7*		nt: Max limit in legal reference when tested according to EN1811:2011-5.	-44\-		$\overline{}$	_	
P1.7"		Article 33 information about substances in articles is available at (add URL or mail cow.lenovo.com/social_responsibility/us/en/environment.html	ntact):	\boxtimes	Ш		
DO							
P2	Batterie		- Control		_		
P2.1*	symbol.	oduct contains a battery or an accumulator, the battery/accumulator is labeled with the Information on proper disposal is provided in user manual. (See legal reference)			Ш		
P2.2*	Batteries reference	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmiu e)	m. (See legal		Ш		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)				\boxtimes	
P3		nity verification & Eco design (ErP)					
P3.1*	The prod	duct is CE-marked to show conformance with applicable legal requirements (see lega	l reference).				
	The Dec	laration of Conformity can be requested at (add link or e-mail address):					
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).					
		d information is; given in item P15 or added to this document,				\boxtimes	
	rtoquilot	available at (add URL):					
P5	Product	packaging					
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercury,	cadmium and				
. 0. 1	hexavale	ent chromium by weight of these together.					
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature of e legal reference).					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).						
		nt: Legal reference has no maximum concentration values.					
P6		nt information					
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		\boxtimes			

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	65D6	Logo	Lanava
Issue date *	2017/4/5		Leilovo

Environmental Conscious design Requirement met	Product	t environmental attributes - Market requirements (See General NOTE GN below)						
Pr. 1		- Environmental conscious design	Require	ment	met			
Pr.1* Parts that have to be treated separately are easily separable Pr.2* Plastic materials in covers/housing have no surface coating. Pr.3* Plastic parts > 20 g consist of one material or of easily separable materials. Pr.4* Plastic parts > 25 g have material codes according to ISO 11489 referring ISO 1043-4. Pr.5* Plastic parts > 25 g have material codes according to ISO 11489 referring ISO 1043-4. Pr.5* Plastic parts > 25 g have material codes according to ISO 11489 referring ISO 1043-4. Pr.5* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Pr.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Pr.6* Upgrading can be done e.g. with processor, memory, cards or drives Pr.9* Spare parts are available after end of production for: 3 years Pr.9* Spare parts are available after end of production for: 3 years Pr.10* Service is available after end of production for: 3 years Pr.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements Pr.12* Insulation materials of external electrical cables are PVC free. Pr.13* Insulation materials of internal electrical cables are PVC free. Pr.14* External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviryl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 0,1% weight (3000 ppm) chlorine attributable to brominated flame retardants in parts containing more than 25% post-consumer recycled content. Printed circuit boards, PCBs (without components) are low halogen: all ∑ PCBs > 25 g are low halogen as defined in IEC of 1249-221. (See INOTE B2) Pr.16* Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Pr.18* Alt. 2: Chemical specifications of flame retardants in pinted circuit bo			Yes	No	n.a.			
P7.1º Parts that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic materials in covers/housing have no surface coating. P7.4º Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P1.50 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P1.50 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P1.50 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6º Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7º Upgrading can be done e.g. with processor, memory, cards or drives P7.8º Upgrading can be done using commonly available tools P7.9º Spare parts are available after and of production for. 3 years P7.10 Service is availables after end of production for. 3 years P7.11 Product over/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Mater	P7							
P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 26 p have material codes according to ISO 11469 referring ISO 1043-4. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 3 years Material and substance requirements P7.10* Service is available after end of production for: 3 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: SGCC Material type: POM Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of external electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chlorinde or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in EC6 81249-2-21. See INOTE B3). P7.16 Plame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: MAtt. 2: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive). TBBPA (reactive) (See NOTE B3). Other: chemical name, CAS #: 3. Chemical name: , CAS #: 3. Chem	P7.1*							
P7.4° Plastic parts > 100 g consist of one material or of easily separable materials. P7.4° Plastic parts > 25 g have material codes according to 150 11469 referring ISO 1043-4. P1.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9° Spare parts are available after end of production for: 3 years P7.10° Service is available after end of production for: 3 years P7.10°				∺				
P7.4 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.7 Product lifetime P7.7 Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 3 years P7.10 Service is available after end of production for: 3 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: SGCC Material type: POM Material type: ABS Material type: SGCC Material type: POM Material								
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labeis are easily separable. (This requirement does not apply to safety/regulatory labeis). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 3 years P7.10 Service is available after end of production for: 3 years P7.11 Material and substance requirements P7.11 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (1000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 P7.16 E1.12 P7.16 E1.12 E1.12 P7.16 E1.12				∺	H			
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product [rifetime Upgrading can be done e.g. with processor, memory, cards or drives Upgrading can be done using commonly available tools West of the production for: 3 years West of the production for: 3 years P7.10 Service is available after end of production for: 3 years Waterial and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum); Material and substance requirements Material type: SGCC Material type: POM Material type: ABS Material type: SGCC Material type: POM Material type: ABS Material type: SGCC Material type: POM Material type: Material so of internal electrical cables are PVC free. West of the production materials of internal electrical cables are PVC free. West of the production materials of internal electrical cables are PVC free. West of the production of the product (production of the product (production production of the product (production of the product (production of the product (production of the product (production of the product (produc				H				
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9° Spare parts are available after end of production for: 3 years P7.10° Service is available after end of production for: 3 years Material and substance requirements P7.11° Material type: ABS P7.12° Insulation materials of external electrical cables are PVC free.				+	H			
P7.8" Upgrading can be done e.g. with processor, memory, cards or drives		3 1 (1 113 3 3 3 7						
P7.8* Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 3 years P7.10 Service is available after end of production for: 3 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: SGCC Material type: POM Insulation materials of internal electrical cables are PVC free.	P7.7*			П	X			
P7.9 Spare parts are available after end of production for: 3 years P7.10 Service is available after end of production for: 3 years Material and substance requirements P7.11	P7.8*			Ħ	X			
P7.10 Service is available after end of production for: 3 years Material and substance requirements								
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: SGCC Material type: POM P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%					Ħ			
P7.11* Product cover/housing material type (e.g., plastics, metal, aluminum): Material type: ABS Material type: SGCC Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2; Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1; Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2; Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content		·						
P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all ☑ PCBs > 25 g ☐ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: ☐ ☑ Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): ☐ TBBPA (additive), ☐ TBBPA (reactive) (See NOTE B3), ☐ Other: chemical name, CAS #: ☐ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑ ☑	P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):						
P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:								
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all \(\) PCBs > 25 g \(\) are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): \[\begin{array}{ c c c c c c c c c c c c c c c c c c c			<u> </u>	<u>Ц</u>				
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #:				<u> </u>				
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20 Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%.	P7.14							
as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive). TBBPA (reactive) (See NOTE B3). Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%.			3					
Marking: Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: CAS #: (See NOTE B4) 2. Chemical name: CAS #: " 3. Chemical name: CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%.	P7.15		า 🗌	\boxtimes				
TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%.	P7.16							
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or	P7.17				\boxtimes			
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or								
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or								
1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or	P7.18		n					
2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or				Ш	\boxtimes			
3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or								
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or								
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or		Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:			\boxtimes			
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or	P7.19			$\overline{\Box}$				
P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or			_					
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or								
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or 	P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):	\boxtimes					
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 26.7%. or 		If YES: at least one of the two alternatives below shall be answered:						
or		a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as						
		. , , , , , , , , , , , , , , , , , , ,						

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	65D6	Logo	Lonovo
Issue date *	2017/4/5		Lei Iovo.
	-		

Product environmental attributes - Market requirements (continued)	Requi	remer	nt met
Item	Yes	No	n.a.

	Material and subs	Material and substance requirements (continued)						
P7.21*	Biobased plastic n	naterial content is use	ed in the product (See No	OTE B7):				
	If YES; at least on	If YES; at least one of the two alternatives below shall be answered;						
		f total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of						
	•	tic by weight) is %.						
	or b) The weight o	The weight of the biobased plastic material is g.						
P7.22*	Light sources are free from mercury, i.e. less than 0,1 mg/lamp.							
1 7.22		nercury is used specify: Number of lamps: and maximum mercury content per lamp: mg						
P8	Batteries							
P8.1*	Battery chemical of	composition:						
P9		tion (See NOTE B8)						
P9.1	For the product the	e following power leve	els or energy consumption	ons are reported:	_			
Energy mo	de *	Power level at	Power level at	Power level at	Reference/Standard for energy			
		100 V AC	115 V AC	230 V AC	modes and test method *			
	STAR® On Mode*	14.80 W	14.77 W	15.03 W	ENERGY STAR® Program Requirements for Computer			
(System Id	le)				Monitors: Ver. 7.0			
ENERGY	STAR® Low Power	0.303 W	0.233 W	0.303 W	ENERGY STAR® Program			
Sleep Mod					Requirements for Computer			
C .00p0u					Monitors: Ver. 7.0			
ENERGY S	STAR® Off /	0.175 W	0.183 W	0.265 W	ENERGY STAR® Program			
Apparent C					Requirements for Computer			
					Monitors: Ver. 7.0			
PTEC *		W	W	W				
	ergy Consumption	47 4 130/1-/	40.015/0//5/5555	47.0130///-/				
ETEC * Annual Energy Consumption		47.1 kWh/year	46.6 kWh/year	47.8 kWh/year				
		ncv Level (Internationa	al Efficiency Marking Pro	otocol) * : 6				
		,			ENERGY STAR® Program			
Display res	solution* : 2.1 mega	apixels			Requirements for Computer			
., .,					Monitors: Ver. 7.0			
					ENERGY STAR® Program			
Default tim	e to enter energy sa	ave mode: 0.5 minute	es		Requirements for Computer			
D0.0*	lafamastian abaut	Alan	tion in annual de de la collection o		Monitors: Ver. 7.0			
P9.2*			tion is provided with the					
P9.3*		s the energy requirem version: 7.0 Product	nents of the following vol	untary program/s:				
P10	Emissions	version. 7.0 Froduct	category. Display.					
		- Declared according	to ISO 9296 (See NOTE	B9)				
P10.1		Mode description	()	Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)				
	Idle *	•		*				
	Operation *			*				
	Other mode L	Declared A-weighted sou	nd pressure level (dB) $L_{p{\sf Am}}$	(operator po	sition desktop – idle)			
	Other mode L	Declared A-weighted sou	nd pressure level (dB) L_{pAm}	(operator position desktop – operating)				
Measured according to: SO 7779 ECMA-74					3/			
	ivieasured accordi		ECMA-74	ECMA 74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *	65D6				Logo	Long	1/0	
Issue date *	2017/4/5					Lenc		тм
Product enviro	nmental attribute	s - Market requiren	ments (continu	ıed)		Require	ment	met
Item						Yes	No	n.a.
Electr	omagnetic emissio	ns						
P10.4 Comp progra		e requirement for low	frequency electr	omagnetic fields of the fo	ollowing volunta	ıry		\boxtimes
	Ergonomics for computing products							
P12.1* The di	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.							
P12.2* The pl	ysical input device r	meets the requirements	ts of ISO 9995 ar	id ISO 9241-410.				\boxtimes
P13 Packa	ging and documen	tation						
Produ	et packaging materia et packaging materia et packaging materia	ıl type(s): <i>PE bag</i>	weight (kg): 0. weight (kg): 0. weight (kg): 0.	0187				
P13.2* Produ	ct plastic primary pac	ckaging is free from PV	VC.			\boxtimes		
	oduct primary corru		kaging, specify t	he contained percentag	e of minimum	post-		
Ùser a		item if paper documer ntation on paper media						
	chlorine-free ntal chlorine-free							
Proce	sed chlorine-free							
P14 Volun	ary programs							
P14.1 The pi	oduct meets the req	uirements of the follow	ving voluntary pro	ogram(s):				
Eco-la Eco-la	bel:	Criteria version: Criteria version: Criteria version:	Da Da Da	te: Produc	t category: t category: t category:			
	onal information (S							
				cription of the tested p				
inform knowle provid	NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implied, regarding the information contained in this document. All information provided by supplier in this document is provided based on supplier's knowledge available at the time of completion, and supplier shall have no obligation to update such information. The information provided here is approximate and provided for informational purposes only. See a Lenovo Account Representative for more information.							ion
		Monitors & Displays fo //products/office_equip		mation:				
	·							

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1