

Annex B2 - Product environmental attributes Computers and computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs		Lenovo
e-mail address	Alvin L Carter		LEIIUVU
	alcarter@Jenovo.com		
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/		
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

	based on product specification or test results based obtained from sample testing), that the product nts given in this declaration.
Type of product *	Notebook Computer
Commercial name *	ThinkPad L14 Gen 4
Model number *	21H5,21H6
Issue date *	2023-03-03
Intended market *	🛛 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Item P1 Ha P1.1* Pr P1.2* Pr CC P1.3* Pr hy tri CC P1.3* Pr P1.5* Pr P1.6* Pa CC P1.7* Rt DI P2 Ba P2.1* If f Sy P2.2* Ba re P2.3* Ba P2.4* Do	vironm roducts of roducts of comment roducts of ydrobron ichloroet oncentra roducts of erphenyl roducts of hain con arts with see legal comment EACH A ttps://wn isclosu	to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. To not contain more th (PCT) in preparations to not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	reparations at European RoHS I tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai er mass of chlorine skin contact do not	Directive. (See legal reference). entration value. ces: Chlorofluorocarbons (ircarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB),	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	. 1,1,1- m red	A quirer Yes		
Item P1 Ha P1.1* Pr P1.2* Pr CC P1.3* Pr P1.3* Pr P1.3* Pr P1.5* Pr P1.5* Pr P1.6* Pa CC P1.7* Rt P1.6* Pa P2 Ba P2.1* If f Sy P2.2* Ba P2.3* Ba P2.4* Do	azardou roducts of roducts of comment roducts of ydrobron ichloroet oncentra roducts of erphenyl roducts of hain con arts with see legal comment EACH A ttps://wn isclosu	s substances and p to comply with curren to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. to not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	reparations at European RoHS I tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai er mass of chlorine skin contact do not	Directive. (See legal reference). entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal reference)	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	Re .1,1,1- m	Yes Yes	nent	met
Item P1 Ha P1.1* Pr P1.2* Pr CC P1.3* Pr P1.3* Pr P1.3* Pr P1.4* Pr P1.5* Pr P1.6* Pa CC P1.7* Rt P1.6* P2 P2.2* Ba P2.2* Ba P2.3* Ba P2.4* Do	azardou roducts of roducts of comment roducts of ydrobron ichloroet oncentra roducts of erphenyl roducts of hain con arts with see legal comment EACH A ttps://wn isclosu	s substances and p to comply with curren to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. to not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	reparations at European RoHS I tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai er mass of chlorine skin contact do not	Directive. (See legal reference). entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal reference)	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	. 1,1,1- m red			
P1 Ha P1.1* Pr P1.2* Pr Co Co P1.3* Pr hy tri co Co P1.3* Pr hy tri co Co P1.4* Pr ch Co P1.6* Pa CO Co P1.7* Ri Di Sy P2.1* If fi Sy P2.2* P2.3* Ba P2.4* Do	roducts (roducts (comment roducts (ydrobron ichloroet oncentra roducts (erpheny) roducts (hain com arts with see legal comment EACH A ttps://w	to comply with curren to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. To not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	t European RoHS I tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai per mass of chlorine skin contact do not	nce). entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal re	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	m red			n.a.
P1.1* Pr P1.2* Pr Co Co P1.3* Pr hy tri co Co P1.4* Pr P1.5* Pr Co Co P1.6* Pa Co Co P1.7* Ri Di Di P2 Ba P2.1* If 1 Sy P2.2* P2.3* Ba P2.4* Do	roducts (roducts (comment roducts (ydrobron ichloroet oncentra roducts (erpheny) roducts (hain com arts with see legal comment EACH A ttps://w	to comply with curren to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. To not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	t European RoHS I tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai per mass of chlorine skin contact do not	nce). entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal re	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	m red			
P1.2* Pr Co P1.3* Pr hy tri- co P1.4* Pr P1.5* Pr P1.5* Pr ch P1.6* Pa Co P1.7* Ri D1 P2 Ba P2.1* If 1 Sy P2.2* Ba P2.3* Ba P2.4* Do	roducts (comment roducts (ydrobron ichloroet oncentra roducts (roducts (hain con arts with see legal comment EACH A ttps://wn	to not contain Asbest Legal reference has to not contain Ozone nofluorocarbons (HBF hane, methyl bromide tion values. To not contain more th (PCT) in preparations to not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	tos (see legal refere no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai ber mass of chlorine skin contact do not	nce). entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal re	(CFC), s, carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference).	m red			
Cd P1.3* Pr hy tri co P1.4* P1.5* Pr P1.6* Pa CO P1.7* P1.7* Ri P1 Pa P2 Ba P2.1* If 1 P2.3* Ba P2.4* Do	comment roducts of ydrobron ichloroet oncentra roducts of erphenyl roducts of hain com arts with see legal comment EACH A ttps://wn	Legal reference has do not contain Ozone hofluorocarbons (HBF hane, methyl bromide tion values. do not contain more th (PCT) in preparations do not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a ww.lenovo.com/us/er	no maximum conce Depleting Substance C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai her mass of chlorine skin contact do not	entration value. ces: Chlorofluorocarbons (rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal re	 carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference). 	m red			
hy cc P1.4* Pr tel P1.5* Pr P1.6* Pa (si Cc P1.7* RI P2 Ba P2.1* If if Sy P2.3* P2.4* Dot	ydrobron ichloroet oncentra roducts erphenyl roducts hain con arts with see legal comment EACH A ttps://wu isclosul	nofluorocarbons (HBF hane, methyl bromide ion values. Io not contain more th (PCT) in preparations to not contain more th aining at least 48% p direct and prolonged reference). Max limit in legal refer tricle 33 information a	C), hydrochlorofluo e (see legal reference han; 0,005% polych s (see legal reference han 0,1% short chai ber mass of chlorine skin contact do not	rcarbons (HCFC), Halons ce). Comment: Legal refer lorinated biphenyl (PCB), ce). in chloroparaffins (SCCP) in the SCCP (see legal re	 carbontetrachloride, rence has no maximur 0,005% polychlorinat with 10-13 carbon ato eference). 	m red			
P1.4* Pr tel P1.5* Pr ch P1.6* Pa (sr Co P1.7* Rf P1.7* Rf P2 Ba P2.1* If f sy P2.2* Ba re P2.3* Ba P2.4* Do	roducts of roducts of hain con- arts with see legal comment EACH A ttps://w	to not contain more the (PCT) in preparations to not contain more the aining at least 48% per- direct and prolonged reference). Max limit in legal refer tricle 33 information a	s (see legal reference han 0,1% short chai per mass of chlorine skin contact do not	ee). in chloroparaffins (SCCP) in the SCCP (see legal re	with 10-13 carbon ato eference).				
P1.5* Pr ch ch P1.6* Pa Co Co P1.7* Rt Di Di P2 Ba P2.1* If ff P2.2* Ba P2.3* Ba P2.4* Do	hain con arts with ee legal comment EACH A ttps://wi bisclosu	to not contain more the aining at least 48% p direct and prolonged reference). Max limit in legal refer rticle 33 information a ww.lenovo.com/us/e	han 0,1% short chai ber mass of chlorine skin contact do not	in chloroparaffins (SCCP) in the SCCP (see legal re	eference).	oms in the	\square		
P1.6* Pa (si CC P1.7* Ri <u>ht</u> P2 Ba P2.1* If i sy P2.2* Ba re P2.3* Ba P2.4* Do	arts with see legal comment EACH A <u>ttps://w</u>	direct and prolonged reference). Max limit in legal refe rticle 33 information a ww.lenovo.com/us/e	skin contact do not						
P1.7* RI htt Di P2 Ba P2.1* If I Sy P2.2* Ba re P2.3* Ba P2.4* Do	EACH A <u>ttps://ww</u> isclosu	rticle 33 information a		according to EN1811:20	11-5.	cm²/week			
P2.1* If 1 sy P2.2* Ba re P2.3* Ba P2.4* Do	ottorica	e	about substances in	articles is available at (ad		:t):			
sy P2.2* Barrer P2.3* Barrer P2.4* Do	atteries								
re P2.3* Ba P2.4* Do				, the battery/accumulator i in user manual. (See lega		posal	\square		
P2.4* Do	atteries eference		ot contain more thar	n 0,0005% of mercury or 0),002% of cadmium. (See legal	\square		
	atteries	and accumulators are	readily removable.	(See legal reference)			\boxtimes		
	ocumen	ation includes the nur	mber of cycles the (secondary) battery can w	ithstand. (See legal re	eference)			
				nnot be "accessed and re external packaging (see l		ssional			
		ty verification & Eco			<u> </u>				
P3.1* Tr Tr <u>ht</u>	he produ he Decla <u>ttps://w</u>	ct is CE-marked to sh	how conformance w can be requested at <u>n/compliance/eu-o</u>			erence).			
P3.2* Th	he produ			gn requirements for energy	y-related products,				
	•	nformation is;		5 or added to this docume I URL): <u>http://www.leno</u> y	,	on	\square		
P5 Pr	roduct p	ackaging		,					
P5.1* Pa he	ackagino exavaler	and packaging comp t chromium by weight	t of these together.	ain more than 0,01% lead			\square		
P5.2* Th	he packa	iging materials are ma legal reference).	arked with abbrevia	tions and numbers indicat	ting the nature of the r	material(s)	\boxtimes		
P5.3* Th Pr Co	he produ rotocol (comment	ct packaging material see legal reference). Legal reference has		depleting substances as sentration values.	specified in the Montr	eal			
		information		able (<i>https://lenovo.com</i> /					

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	21H5,21H6 Logo			
lssue da	ate *	2023-03-03	Ler	10	VC
Produc	- Envire	onmental attributes - Market requirements (See General NOTE GN below)	Require	ement	met
ltem		tory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7	Design				
P7.1*		mbly, recycling at have to be treated separately are easily separable			
P7.2*		naterials in covers/housing have no surface coating.			
P7.3*		parts > 100 g consist of one material or of easily separable materials.			⊢
P7.4*	•	parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		<u> </u>	
P7.4 P7.5				<u> </u>	<u> </u>
P7.5 P7.6*		parts are free from metal inlays or have inlays that can be removed with commonly available tools.		<u> </u>	
P7.6"		are easily separable. (This requirement does not apply to safety/regulatory labels).			
P7.7*		t lifetime ng can be done e.g. with processor, memory, cards or drives			_
P7.8*		ng can be done using commonly available tools		<u> </u>	╞
P7.8 P7.9	18		\square		<u> </u>
		arts are available after end of production for: 5 years			<u> </u>
P7.10		is available after end of production for: 5 years			
P7.11*		l and substance requirements cover/housing material type (e.g. plastics, metal, aluminum):			
F7.11		type: <i>AL</i> Material type: <i>PC/ABS</i> Material type: <i>PC/CF</i>			
P7.12		n materials of external electrical cables are PVC free.		\square	
P7.13	Insulatio	n materials of internal electrical cables are PVC free.			Ħ
P7.14	weight (polyviny	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and I chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts ng more than 25% post-consumer recycled content.			
P7.15	Printed of	circuit boards, PCBs (without components) are low halogen: all ☐ PCBs > 25 g	\boxtimes		
P7.16	Marking				
P7.17		hemical specifications of flame retardants in printed circuit boards > 25 g (without components): (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: <i>DOPO-HQ</i> , CAS #: <i>0-1</i>			
		hemical specifications of flame retardants in printed circuit boards (without components) > 25 g ig ISO 1043-4:			
P7.18	Alt. 1: Fl concent 1. Chem 2. Chem	ame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in rations above 0,1%: nical name: , CAS #: (See NOTE B4) nical name: , CAS #: " nical name: , CAS #: "			
P7.19	In plastic assigned	hemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: <i>FR(40)</i> c parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been d the following Risk phrases; and Hazard statements:			
		rce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

	mber *	21H5,21	16			Logo			
lssue dat	e *	2023-03-	03				.en	0	VO
	environ	mental at	tributes - Market I	requirements (cont	inued)		Requir		
Item							Yes	No	n.a.
P7.20*			tance requirements			.)			
11.20	lf YES; a) Of pe or	at least one total plastic rcentage of	of the two alternative	nt) is 15.53% .	vered;). content (calculated as a			
P7.21*	Biobase If YES; a) Of	ed plastic m at least one total plastic	aterial content is use of the two alternativ parts' weight > 25 g	d in the product (See Nes below shall be answ	vered;	ated as a percentage of			
	or	al plastic by e weight of	weight) is %. %. %.	material is g.					
P7.22*			ree from mercury, i.e specify: Number of la	. less than 0,1 mg/lamp mps: and maxir	o. num mercury content p	per lamp: mg	\boxtimes		
P7.23*				ne total mercury conter				\square	
P8	Batteri		5 1),	,	<u> </u>				
P8.1*			omposition: Lithium	ion					
P9	Energy	consumpt	ion (See NOTE B8)						
P9.1				els or energy consumpt	ions are reported:				
Energy m	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard modes and test meth		у	
Peak (On	-Max)		100 W	100 W	100 W	Full Load			
Device Ca	ategory 2								
Short Idle Enabled (NOL	6.960 W	6.972 W	6.888 W	ENERGY STAR Con	nputers	V8.0	
Long Idle Enabled (VOL	1.272 W	1.368 W	1.188 W	ENERGY STAR Con	nputers	V8.0	
Sleep (S3 (P _{Sleep})			1.272 W	1.368 W	1.188 W	ENERGY STAR Con	nputers	V8.0	
Off Mode Disabled		OL	0.432 W	0.432 W	0.456 W	ENERGY STAR Con	nputers	V8.0	
PTEC *	nergy Con	sumption	W	W	W				\square
ETEC * Annual Er			21.76 kWh/year	22.21 kWh/year	21.29 kWh/year	$E_{TEC} = (8760/1000) \times P_{sleep} \times 0.05 + P_{long_{ld}} \\ P_{short_{ldle}} \times 0.35)$	_{lle} x 0.15-	F	
ETEC * Annual Er				22.21 kWh/year al Efficiency Marking P		P _{sleep} x 0.05 + P _{long_ld}	ncy Marl	⊦ king	
ETEC * Annual Er External F	Power Sup		cy Level (Internation			P _{sleep} x 0.05 + P _{long_la} P _{short_ldle} x 0.35) International Efficie Protocol (IEMP) for	ncy Marl	⊦ king	
Display re	Power Sup	ply Efficien	cy Level (Internation			$\begin{array}{c} P_{sleep} \times 0.05 + P_{long_ld} \\ P_{short_ldle} \times 0.35 \end{array}$ International Efficie Protocol (<i>IEMP</i>) for Power Supplies	ncy Marl External	king	
ETEC * Annual Er External F Display re	Power Sup solution * ne to ente	pply Efficien : 2.074 me r energy sa	cy Level (Internationa gapixels ve mode: 5 minutes		rotocol) * : VI	$\begin{array}{c} P_{sleep} \times 0.05 + P_{long_{ld}} \\ P_{short_{ldle}} \times 0.35 \end{array}$ International Efficie Protocol (<i>IEMP</i>) for Power Supplies 1920*1080	ncy Marl External	king	

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	21H5,21H6	Logo	
Issue date *	2023-03-03		Lenovo

	environmenta	l attributes - Market requirements (co	munueu)		equire		
Item					Yes	No	n.a
P10	Emissions						
		n – Declared according to ISO 9296 (See No					
P10.1	Mode	Mode description	Statistical uppe L _{WA,c} (B)	er limit A-weighted sound powe	er level,		
	Idle	* Idle Mode	* 2.7			[
	Operation	* Operating (CPU)	* 3.5			[
	Other Mode	Declared A-weighted sound pressure level (dB)	17 (operator p	osition desktop – idle)			
	Other mode	Declared A-weighted sound pressure level (dB) L _{pAm}	27.9 (operator	position desktop – operating-CP	יט)		
	Measured acco	ording to: XISO 7779 ECMA-74 Other (only if not covered	ed by ECMA-74)				
	Electromagne						
P10.4	program(s): M	ay meets the requirement for low frequency (PR-II(3 pin AC adapter only)	electromagnetic fields	s of the following voluntary	\square		
P12		or computing products					
P12.1*		ets the ergonomic requirements of ISO 9241			\square		
P12.2*		put device meets the requirements of ISO 99	995 and ISO 9241-41	Э.	\boxtimes		
P13		d documentation					
P13.1*	Product package	ging material type(s): <i>Paper</i> weight (k	(g): 0.3698 (g): 0.1512 (g): 0.0129				
P13.2*		primary packaging is free from PVC.			\boxtimes		
P13.3*		mary corrugated fiberboard packaging, speci vered fiber content: 60 %	fy the contained perce	entage of minimum post-			
P13.4*	Specify media	for user and product documentation (tick box Paper 🔀, Other 🗌):				
P13.5		omplete this item if paper documentation used act documentation on paper media is chlorine specify:					
	Totally chlorine	-free					
	Elemental chlo						
	Processed chlo	prine-free					
P14	Voluntary prog	grams					
P14.1	The product me	eets the requirements of the following volunta	ary program(s):			_	
	ENERGY STAI Eco-label: EPE		Date: 2023/01/03 Date: 2023/03/06	Product category: 2 Product category: <i>Notebook</i>			
	Eco-label: TCC		Date: 2023/4/20	Product category: Notebook			
P15	Additional info	ormation (See NOTE B10)					
P 9		mption of computer products; descriptior	a of the tested was de				

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

Lenovo ErP Lot26 Information Sheet - Network Equipment -

As required by_

- Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off-mode electric power consumption of electrical and electronic household equipment (ErP Lot 6)
- Commission Regulation (EU) No 801/2013 of 22 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for (ErP Lot 26).

Products scope of this sheet:

Notebook/Tablet Computer < 6 W Idle

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad L14 Gen 4	Logo
Model Number	21H4,21H5	
Product Type	Notebook Computer with Idle Power < 6 W	Lenovo
Issue Date	2023-03-03	
Additional information		

P7.1.1 Product environmental attributes

	year of manufacture:	2023
)	Network Standby Classification	LoNA Equipment
	Off Mode Power (Watts)	0.46 Watts
	Standby Mode	Watts Mode Not Applicable
		minutes Default Delay Time
	Description of how to enable Network Standby Mode	Network Standby Mode is enabled at Shipment
	Description of how to manually enter Network Standby Mode	1) Press the Power Button once
		2) Click on the Power Button and choose Sleep
	Default Delay time to Network Standby Mode	7.5 minutes
	Reactivation Function from Network Standby Mode	Open Notebook, Press Keyboard or power button, activate USB

Network Port	Wired Ethernet	Wireless Ethernet	USB-A	USB-C	HDMI	BlueTooth	Other: Nano SIM			
Present in Product										
Activated at Shipment										
Active in Network Standby Mode										
Location of Network Port	Left	N/A	Left and Righ	Left	Left	N/A	Right			
Network Port Maximum Performance	1.00 GB/s	0.15 GB/s	GB/s	GB/s	GB/s	GB/s	GB/s			
Network Protocol	802.3	Wi-Fi 6; 802.11ax	USB 3.2 Gen 1	USB 3.2 Gen 1;USB 3.2 Gen 2		BT5.2	4G			
Network Standby Mode Power	1.19Watts	1.19Watts	Watts	Watts	Watts	Watts	Watts			
Network Standby										
Power – All				1.19Watts						
Active				1.19Walls						
Connections Additional Informa		nd disconnecti	ng from wireles	ss networks is inc	luded in the	User Manual				
Additional Informa	connecting to a		ng from wirele:	ss networks is inc	luded in the	User Manual				
Additional Informa	connecting to a			ss networks is inc 24.8 degree Celsiu		User Manual				
Additional Informa Instructions on o	connecting to an or measurement ature,	s,				User Manual				
Additional Informa Instructions on o Test parameters f ambient tempera	connecting to an or measurement ature, and frequency in	s, n Hz,		24.8 degree Celsiu		User Manual				
Additional Informa Instructions on o Test parameters f ambient tempera test voltage in V total harmonic d information and up and circuits u	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica	s, n Hz, ectricity supply n the instrumer testing	system,	24.8 degree Celsiu 230 V / 50 Hz	15	User Manual				
Additional Informa Instructions on o Test parameters fr ambient tempera test voltage in V total harmonic d information and up and circuits u External power su	or measurement ature, and frequency in istortion of the el documentation c sed for electrica pply efficiency (i	s, n Hz, ectricity supply n the instrumer testing f applicable)*:	system, tation, set-	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210	15					
Additional Informa Instructions on o Test parameters f ambient tempera test voltage in V total harmonic d information and up and circuits u	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica	s, ectricity supply on the instrumer l testing f applicable)*: Output	system,	24.8 degree Celsiu 230 V / 50 Hz <2%	15	ad No I	Load wer 27 W			
 Additional Informa Instructions on o Test parameters fr ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Output Voltage 20 V 20 V	s, h Hz, ectricity supply in the instrumer l testing f applicable)*: Output Current 2.25 A 2.25 A	system, tation, set- Power 45 W 45 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89%	10% Lo Efficien 89% 89%	ad No I icy Po 0.00 0.03	wer 27 W 32 W			
Additional Informa Instructions on o Test parameters fr ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Voltage 20 V 20 V	s, h Hz, ectricity supply in the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A	system, tation, set- Power 45 W 45 W 45 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89%	10% Lo Efficien 89% 89%	ad No I icy Po 0.02 0.03 0.03	wer 27 W 32 W 1 W			
Additional Informa Instructions on o Test parameters for ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel Delta	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Voltage 20 V 20 V 20 V 20 V 20 V	s, ectricity supply in the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A	System, tation, set- Output Power 45 W 45 W 45 W 45 W 65 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 90%	10% Lo Efficien 89% 89% 88% 88% 90%	ad No I icy Po 0.00 0.00 0.01 0.01	wer 27 W 32 W 1 W 17 W 25 W			
Additional Informa Instructions on o Test parameters for ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel Delta Chicony	connecting to an or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Output Voltage 20 V 20 V 20 V 20 V 20 V 20 V	s, ectricity supply in the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A	System, tation, set- Output Power 45 W 45 W 45 W 65 W 65 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89%	10% Lo Efficien 89% 89% 88% 90% 89%	ad No I Icy Po 0.00 0.00 0.00 0.00 0.00 0.00	wer 27 W 32 W 1 W 17 W 25 W 29 W			
Additional Informa Instructions on o Test parameters for ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel	connecting to all or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Output Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	s, ectricity supply on the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A	System, tation, set- Power 45 W 45 W 45 W 65 W 65 W 65 W 65 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89% 89%	10% Lo Efficien 89% 89% 88% 88% 90% 90% 90%	ad No I icy Po 0.02 0.03 0.01 0.01 0.02 0.02 0.02 0.03 0.03	wer 27 W 32 W 1 W 17 W 25 W 29 W 88 W 15 W			
Additional Informa Instructions on c Test parameters for ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel Delta Chicony Liteon Acbel Delta	connecting to all or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	s, ectricity supply on the instrumer testing f applicable)*: Output 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A	System, tation, set- Output Power 45 W 45 W 45 W 65 W 65 W 65 W 65 W 65 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89% 89% 89% 89% 90%	15 10% Lo Efficien 89% 89% 89% 89% 89% 90% 90% 90% 90% 90% 90%	ad No I icy Po 0.02 0.02 0.02 0.02 0.02 0.02 0.02 0.0	wer 27 W 32 W 1 W 17 W 25 W 29 W 88 W 15 W 35 W			
Additional Informa Instructions on o Test parameters for ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel	connecting to all or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Output Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	s, ectricity supply on the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A 3.25 A 3.25 A	System, tation, set- Power 45 W 45 W 45 W 65 W 65 W 65 W 65 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89% 89%	10% Lo Efficien 89% 89% 88% 88% 90% 90% 90%	ad No I icy Po 0.02 0.02 0.02 0.02 0.02 0.02 0.02 0.0	wer 27 W 32 W 1 W 17 W 25 W 29 W 88 W 15 W			
Additional Informa Instructions on c Test parameters fr ambient tempera test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel Delta Chicony Liteon Acbel Delta Chicony	connecting to all or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	s, h Hz, ectricity supply in the instrumer testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25	System, tation, set- tation, set- tation, set- Output Power 45 W 45 W 45 W 65 W 65 W 65 W 65 W 65 W 65 W 100 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89% 89% 89% 89% 89%	15 10% Lo Efficien 89% 89% 89% 89% 89% 90% 90% 90% 90%	ad No I icy Po 0.02 0.03 0.03 0.04 0.05 0.05 0.05 0.05 0.05 0.05 0.05	wer 27 W 32 W 1 W 17 W 25 W 29 W 88 W 55 W 35 W 41 W			
Additional Informa Instructions on control Test parameters for ambient temperative test voltage in V total harmonic d information and up and circuits u External power su Model Delta Chicony Liteon Acbel Delta Chicony Liteon Acbel Delta Chicony Liteon	connecting to all or measurement ature, and frequency in istortion of the el documentation of sed for electrica pply efficiency (i Voltage 20 V 20 V 20 V 20 V 20 V 20 V 20 V 20 V	s, h Hz, ectricity supply n the instrumer t testing f applicable)*: Output 2.25 A 2.25 A 2.25 A 2.25 A 3.25	System, tation, set- Output Power 45 W 45 W 65 W 65 W 65 W 65 W 65 W 65 W 100 W 100 W	24.8 degree Celsiu 230 V / 50 Hz <2% Yokogawa WT210 Average Active Efficiency 89% 89% 89% 89% 89% 89% 89% 89% 89% 89%	15 10% Lo Efficien 89% 89% 89% 88% 90% 90% 90% 90% 90% 90%	ad No I icy Po 0.02 0.03 0.03 0.04 0.05 0.05 0.05 0.05 0.05 0.05 0.05	wer 27 W 32 W 1 W 77 W 25 W 29 W 98 W 55 W 55 W 35 W 41 W 3 W			